

CARBOTROL®

'HI-FLO' CARBON ADSORBERS 5,000 to 20,000 CFM RADIAL FLOW



FEATURES

- High air flow capacity.
- Low pressure drop, approx. 12" wc at maximum flow rate.
- Polypropylene construction with PVC internal piping.
- High activity carbon.

OPTIONS

- "GC" series with catalytic carbon for H₂S removal.
- Interconnecting piping and fan.
- FRP construction.

SPECIFICATIONS

	<u>G-8-PPL</u>	<u>G-12-PPL</u>	<u>G-14-PPL</u>	<u>G-15-PPL</u>	<u>G-17-PPL</u>
MAX. FLOW* (CFM):	5,000	8,000	10,000	14,000	20,000
CARBON (lbs.):	2,450	4,100	6,700	9,900	17,200
APPROX. SIZE:	5'Ø x 7'	6'Ø x 11'	7'Ø x 13'	8'Ø x 13'	10'Ø x 15'
SHIPPING WT (lbs.):	4,000	5,400	8,200	12,000	19,700
INLET/OUTLET (duct):	16"	22"	26"	30"	36"
DESIGN PRESSURE (psi):	3	3	3	3	3

* NOTE: Air flows must be derated for H₂S applications. Please consult CARBTROL.

CARBOTROL provides complete systems ranging from 90 to 20,000 CFM.

© Copyright 2002 Carbtrol Corporation -12/10/08

AT-415/#4

CARBOTROL®
CORPORATION

955 Connecticut Ave., Suite 5202
Bridgeport, CT 06607

800-242-1150 Fax: 203-337-4347
www.carbtrol.com info@carbtrol.com

